

COMPACT, INDUSTRIAL
THERMAL CAMERA

Xenics
EXOSENS GROUP

Ceres V 640 Series



UNCOOLED MICROBOLOMETER CAMERA
FOR HIGH-RESOLUTION THERMAL IMAGING

KEY FEATURES



COMPACT AND HIGH-RESOLUTION



**SUPERIOR ON-BOARD IMAGE
PROCESSING PERFORMANCE**



**FLEXIBLE OPTICAL MOUNT &
LENS OPTIONS***

The Ceres V 640 series is based upon the Dione 640 OEM thermal imaging core with 640x480 pixels and 12 μm pixel pitch. Thanks to the state-of-the-art microbolometer detector and on-board image processing, the camera offers superior thermal imaging capabilities.

The Ceres V 640 camera outputs full frame images at 60 Hz via either a CameraLink or GigE Vision interface - all GenICam compliant. The compact size, excellent image quality and GenICam compliant interfacing allow for easy integration in demanding industrial, scientific and security thermal imaging applications.

*Different lens interface options are available.
For more information, contact us at sales@xenics.com

Ceres V 640 Series



KEY PERFORMANCES

Image format/Pixel pitch	640 x 480 pixels / 12 μ m
Integration type	Rolling Shutter
Spectral range	8 -14 μ m
Max frame rate (full frame)	60 Hz
Power consumption	4 W (GigE); 3.5 W (CL)
Power supply voltage	DC 12 V

FUNCTIONS & INTERFACES

Digital output format	GigE; CL
Operating temperature range (housing temperature)	From -40°C to +70°C
Storage temperature range	From -40 °C to +85 °C
Detector NETD	<50 mK(at 30Hz, 300K, F/1); <40 mK (at 30 Hz, 300 K, F/1), available upon request
Shock / Vibration	40 g, 11 ms, MIL-STD810G/ 5 g (20 to 2000 Hz), MIL-STD810G

PRODUCT SELECTOR GUIDE

XEN-000786 [Ceres V 640 GigE 50 mK (60 Hz)]	XEN-000724 [Ceres V 640 GigE 50 mK (9 Hz)]
XEN-000788 [Ceres V 640 GigE 40 mK (60 Hz)]	XEN-000725 [Ceres V 640 GigE 40 mK (9 Hz)]
XEN-000784 [Ceres V 640 CL 50 mK (60 Hz)]	XEN-000727 [Ceres V 640 CL 50 mK (9 Hz)]
XEN-000787 [Ceres V 640 CL 40 mK (60 Hz)]	XEN-000728 [Ceres V 640 CL 40 mK (9 Hz)]

advancedimaging@exosens.com



exosens.com

EXOSENS
REVEAL THE INVISIBLE